

### **SOLID END CAPS**

# DUPLEX and SUPER DUPLEX STAINLESS STEEL END CAPS

#### **Materials:**

Duplex or Super Duplex stainless steel available both in CE8MN (UNS # J93345) and CE3MN (UNS # J93404) cast grades in accordance with ASTM A995/A995M.

#### Working Pressure1:

Nominal size	Working Pressure <sup>1</sup>		
3/4" - 6"	1200 psi (82 bar)		
8" - 12"	1000 psi (69 bar)		

<sup>\*</sup>Contact Piedmont for higher pressure options with larger end caps.

## 316 STAINLESS STEEL END CAPS Materials:


Duplex or Super Duplex stainless steel available both in CE8MN (UNS # J93345) and CE3MN (UNS # J93404) cast grades in accordance with ASTM A995/A995M.

#### Working Pressure1:

Nominal size	Working Pressure <sup>1</sup>		
3/4" - 6"	600 psi (40 bar)		
8" - 12"	400 psi (28 bar)		

<sup>\*</sup>Contact Piedmont for higher pressure options with larger end caps.

<sup>1</sup>Working pressures have been determined based on generally accepted standard specifications for performance of gasketed mechanical couplings, in accordance with ASTM F1476 standard and are applicable for schedule 40s (or thicker) cut grooved pipes and flexible couplings rated for the stated working pressure. Some of the endcaps can be rated for higher pressure. Consult with Piedmont for applications requiring higher pressure than the specified working pressure, pipes with thinner schedule and pipes with roll grooves. Pipe's schedule, working pressure and material must comply with the requirements of ASME B31.1.



Stainless Steel End Caps - F Specifications						
Nominal	Dimensions				Approx.	
size	inch				weight	
(inch)	(mm)				lb	
	OD	С	В	А	(kg)	
3/4	1.05	0.94	0.31	0.63	0.22	
	(26.7)	(23.9)	(7.9)	(16.0)	(0.10)	
1	1.32	1.19	0.50	0.63	0.40	
	(33.4)	(30.2)	(12.7)	(15.9)	(0.18)	
1-1/4	1.66	1.54	0.50	0.63	0.64	
	(42.2)	(39.0)	(12.7)	(15.9)	(0.29)	
1-1/2	1.90	1.78	0.50	0.63	0.72	
	(48.3)	(45.1)	(12.7)	(15.9)	(0.33)	
2	2.38	2.25	0.50	0.63	1.34	
	(60.3)	(57.2)	(12.7)	(15.9)	(0.61)	
2-1/2	2.88	2.72	0.50	0.63	1.93	
	(73.0)	(69.1)	(12.7)	(15.9)	(0.88)	
3	3.50	3.34	0.50	0.63	2.96	
	(88.9)	(84.9)	(12.7)	(14.9)	(1.34)	
4	4.50	4.33	0.50	0.63	4.98	
	(114.3)	(110.1)	(12.7)	(16.0)	(2.26)	
6	6.63	6.46	0.50	0.63	11.76	
	(168.3)	(164.0)	(12.7)	(16.0)	(5.33)	
8	8.63	8.44	0.63	0.75	21.74	
	(219.1)	(214.4)	(16.0)	(19.1)	(9.86)	
10	10.75	10.56	0.75	0.75	37.31	
	(273.1)	(268.3)	(19.1)	(19.1)	(16.93)	
12	12.75	12.50	0.75	0.75	52.58	
	(323.9)	(317.5)	(19.1)	(19.1)	(23.85)	