

## FLEXIBLE HOSE DATA SHEET

**EASYFLEX Flexible Sprinkler Drops are designed to significantly reduce labor and installation costs. By eliminating the need for pipe cutting and midline connections, you save valuable time and money.**

EASYFLEX Flexible Sprinkler Drops can be installed on almost any suspended commercial ceilings. The flexible hose allows for fast installation while our innovative brackets are simple and easy to install. Brackets for T-Bar ceiling grids, wall mount, metal studs, woodbeams, open hat channels, industrial ducts, and cleanrooms. No special tools required, and installation completed in a few easy steps.

Flexible hoses come in braided or unbraided types, from 24" to 72" in length.

### EASYFLEX Flexible Sprinkler Drops Appliance Standards

- **National Fire Protection Association (NFPA):**
  - NFPA 13: Standard for the Installation of Sprinkler Systems
  - NFPA 13D: Standard for the Installation of Sprinkler Systems in One and Two-Family Dwellings and Manufactured Homes
  - NFPA 13R: Standard for Installation of Sprinkler Systems in residential Occupancies up to and including four stories in height
- **American Society for Testing and Methods (ASTM):**
  - ASTM C635: Standards specifications for the manufacture, performance, and testing of metal suspension systems for acoustical tile and lay-in panel ceilings
  - ASTM C636: Standards practice for installation of metal ceiling suspension systems for acoustical tile and lay-in panels
- **Factory Mutual (FM), FM Class No. 1637:** Approved standard for flexible sprinkler hose with threaded end fittings
- **Underwriter's Laboratories, Inc. (UL/ULC), cULus 2443:** Standards for flexible sprinkler hose with fittings for fire protection services

### TECHNICAL DATA

Maximum Working Pressure Rating	175 psig UL/ULC/FM		Minimum Bending Radius	4" (UL/ULC) and 8" (FM) * <b>DO NOT</b> bend within 2.52 inches from connection nuts	
Maximum Ambient Temperature Rating	225°F				
Connection	Inlet	1" NPT	K-Factor	½" Outlet	5.6
	Outlet	½" or ¾" NPT		¾" Outlet	8.0

\* No hangers and seismic escutcheons required

\* Required torque to assemble reducer and nipple with the flexible hose: 50 feet per pound

### SUBMITTAL

Job Name		Job Location	
Submitted By		Date	
Approved By		Date	

