


MODEL 7721 MECHANICAL TEE, FEMALE THREADED OUTLET

The Model 7721 Mechanical Tee when mounted on hole cut pipe provides a fast and easy mid-pipe threaded branch outlet. By utilizing the Model 7721 you eliminate the need for welding or the use of multiple fittings. The Mechanical Tee is comprised of upper and lower ductile iron housing segments, a grade "E" EPDM rubber molded gasket and plated track bolts and nuts. Mechanical tees are supplied with our standard painted finishes, i.e. orange or RAL3000 red. Optional finishes such as hot dipped zinc galvanized and custom epoxy coatings are also available.



For Fire Protection pressure rating, listing, and approval information, refer to Data Sheet B-42 or visit **SHURJOINT** website, www.shurjoint.com for details or contact your **SHURJOINT** Representative.



Full warranty terms can be found on www.shurjoint.com

Model 7721 Mechanical Tee, Female Threaded Outlet

Nominal Size Run x Branch	Max. Working Pressure (CWP)*	ASME/ANSI Pressure Class Rating^ @100°F@38°C	Hole Dia. F +0.13, -0 / +3.2, -0	Dimensions				Bolt Size	Weight	
				T#	A	B	C			D
in mm	PSI Bar	PSI Nom. Class	in mm	in mm	in mm	in mm	in mm	in mm	Lbs Kgs	
2 x 1/2 50 x 15	300 20	300 150	1.50 38	1.97 50	2.50 64	1.57 40	5.04 128	2.87 73	3/8 x 2 1/8 M10 x 55	2.4 1.1
2 x 3/4 50 x 20	300 20	300 150	1.50 38	1.97 50	2.50 64	1.57 40	5.04 128	2.87 73	3/8 x 2 1/8 M10 x 55	2.4 1.1
2 x 1 50 x 25	300 20	300 150	1.50 38	2.00 51	2.68 68	1.57 40	5.04 128	2.87 73	3/8 x 2 1/8 M10 x 55	2.6 1.2
2 x 1 1/4 50 x 32	300 20	300 150	[1.75] [45]	2.08 53	2.80 71	1.57 40	5.04 128	3.22 82	3/8 x 2 1/8 M10 x 55	2.9 1.3
2 x 1 1/2 50 x 40	300 20	300 150	[1.75] [45]	2.08 53	2.80 71	1.57 40	5.04 128	3.22 82	3/8 x 2 1/8 M10 x 55	2.9 1.3
2 1/2 x 1/2 65 x 15	300 20	300 150	1.50 38	2.25 57	2.80 71	1.89 48	5.75 146	2.87 73	1/2 x 3 M12 x 75	3.1 1.4
2 1/2 x 3/4 65 x 20	300 20	300 150	1.50 38	2.32 59	2.88 73	1.89 48	5.75 146	2.87 73	1/2 x 3 M12 x 75	3.1 1.4
2 1/2 x 1 65 x 25	300 20	300 150	1.50 38	2.28 58	2.95 75	1.89 48	5.75 146	2.87 73	1/2 x 3 M12 x 75	3.3 1.5
2 1/2 x 1 1/4 65 x 32	300 20	300 150	2.00 51	2.40 61	3.11 79	1.89 48	5.75 146	3.22 82	1/2 x 3 M12 x 75	3.5 1.6
2 1/2 x 1 1/2 65 x 40	300 20	300 150	2.00 51	2.40 61	3.11 79	1.89 48	5.75 146	3.22 82	1/2 x 3 M12 x 75	3.5 1.6
3 x 1/2 80 x 15	300 20	300 150	1.50 38	2.47 63	3.19 81	2.20 56	6.39 160	2.63 67	1/2 x 3 M12 x 75	3.5 1.6
3 x 3/4 80 x 20	300 20	300 150	1.50 38	2.44 62	3.19 81	2.20 56	6.39 160	2.63 67	1/2 x 3 M12 x 75	3.5 1.6
3 x 1 80 x 25	300 20	300 150	1.50 38	2.50 64	3.19 81	2.20 56	6.39 160	2.63 67	1/2 x 3 M12 x 75	3.7 1.7
3 x 1 1/4 80 x 32	300 20	300 150	2.00 51	2.80 71	3.50 89	2.20 56	6.39 160	3.46 88	1/2 x 3 M12 x 75	4.2 1.9
3 x 1 1/2 80 x 40	300 20	300 150	2.00 51	2.80 71	3.50 89	2.20 56	6.39 160	3.46 88	1/2 x 3 M12 x 75	4.4 2.0
3 x 2 80 x 50	300 20	300 150	2.50 64	2.83 72	3.58 91	2.20 56	6.39 160	3.98 101	1/2 x 3 M12 x 75	5.1 2.3
4 x 1/2 100 x 15	300 20	300 150	1.50 38	3.00 76	3.70 94	2.83 72	7.48 190	2.63 67	1/2 x 3 M12 x 75	4.2 1.9

Model 7721 Mechanical Tee, Female Threaded Outlet

Nominal Size Run x Branch	Max. Working Pressure (CWP)*	ASME/ANSI Pressure Class Rating^ @100°F@38°C	Hole Dia. \mp +0.13, -0/+3.2, -0	Dimensions					Bolt Size	Weight
				T#	A	B	C	D		
				in mm	in mm	in mm	in mm	in mm		
4 x 3/4 100 x 20	300 20	300 150	1.50 38	2.95 75	3.70 94	2.83 72	7.48 190	2.63 67	1/2 x 3 M12 x 75	4.2 1.9
4 x 1 100 x 25	300 20	300 150	1.50 38	3.03 77	3.70 94	2.83 72	7.48 190	2.63 67	1/2 x 3 M12 x 75	4.4 2.0
4 x 1 1/4 100 x 32	300 20	300 150	2.00 51	3.19 81	3.89 99	2.83 72	7.48 190	3.35 85	1/2 x 3 M12 x 75	4.8 2.2
4 x 1 1/2 100 x 40	300 20	300 150	2.00 51	3.19 81	3.89 99	2.83 72	7.48 190	3.35 85	1/2 x 3 M12 x 75	5.1 2.3
4 x 2 100 x 50	300 20	300 150	2.50 64	3.38 86	4.13 105	2.83 72	7.48 190	3.98 101	1/2 x 3 M12 x 75	5.9 2.7
4 x 2 1/2 100 x 65	300 20	300 150	2.75 70	3.23 82	4.37 111	2.83 72	7.48 190	4.40 112	1/2 x 3 M12 x 75	7.3 3.3
4 x 3 100 x 80	300 20	300 150	3.50 89	3.23 82	4.40 112	2.83 72	7.48 190	5.35 136	5/8 x 3 1/2 M16 x 90	12.3 5.6
5 x 2 125 x 50	300 20	300 150	2.50 64	4.13 105	4.88 124	3.39 86	9.29 236	4.00 102	5/8 x 3 1/2 M16 x 90	9.2 4.2
5 x 2 1/2 125 x 65	300 20	300 150	2.75 70	3.89 99	5.00 127	3.39 86	9.29 236	4.65 118	5/8 x 3 1/2 M16 x 90	9.9 4.5
6 x 1 1/4 150 x 32	300 20	300 150	2.00 51	4.29 109	5.00 127	3.86 98	10.07 256	3.66 93	5/8 x 5 5/16 M16 x 135	9.7 4.4
6 x 1 1/2 150 x 40	300 20	300 150	2.00 51	4.29 109	5.00 127	3.86 98	10.07 256	3.66 93	5/8 x 5 5/16 M16 x 135	9.7 4.4
6 x 2 150 x 50	300 20	300 150	2.50 64	4.45 113	5.29 132	3.86 98	10.07 256	3.98 101	5/8 x 5 5/16 M16 x 135	10.6 4.8
6 x 2 1/2 150 x 65	300 20	300 150	2.75 70	4.37 111	5.50 140	3.86 98	10.07 256	4.65 118	5/8 x 5 5/16 M16 x 135	11.9 5.4
6 x 3 150 x 80	300 20	300 150	3.50 89	4.33 110	5.50 140	3.86 98	10.07 256	5.39 137	5/8 x 5 5/16 M16 x 135	13.2 6.0
6 x 4 150 x 100	300 20	300 150	4.50 114	4.21 107	5.50 140	3.86 98	10.07 256	6.46 164	5/8 x 5 5/16 M16 x 135	14.5 6.6
8 x 2 200 x 50	300 20	300 150	[2.75] [70]	5.31 135	6.54 166	4.72 120	12.87 327	3.98 101	3/4 x 4 3/4 M20 x 120	13.6 6.2
8 x 2 1/2 200 x 65	300 20	300 150	2.75 70	5.39 137	6.54 166	4.72 120	12.87 327	4.09 104	3/4 x 4 3/4 M20 x 120	13.9 6.3
8 x 3 200 x 80	300 20	300 150	3.50 89	5.35 136	6.54 166	4.72 120	12.87 327	5.04 128	3/4 x 4 3/4 M20 x 120	15.6 7.1
8 x 4 200 x 100	300 20	300 150	4.50 114	5.24 133	6.54 166	4.72 120	12.87 327	6.46 164	3/4 x 4 3/4 M20 x 120	17.6 8.0

1. \mp Hole diameters listed are suggested hole diameters.
2. \mp T: Take-Out (Center of run to end of pipe to be engaged.)
3. [] Important: Make special note of the hole saw size and maximum diameter allowed on these sizes, deviation could lead to joint failure.
4. *Working pressure is based on standard wall carbon steel pipe.
5. ^ The ASME/ANSI pressure class rating is not the design or maximum pressure rating, rather is provided for those that are accustomed to specifying or using ASME/ANSI class rated components such as flange, valves, etc.

MATERIAL SPECIFICATIONS

• Housing:

Ductile Iron to ASTM A536, Gr. 65-45-12 and or ASTM A395, Gr. 65-45-15, min. tensile strength 65,000 psi (448 MPa).

• Surface Finish:

- Orange color painted or red RAL3000 color painted.
- Hot dip galvanized (Option).
- Epoxy coated in red RAL3000 or other colors (Option)

• Rubber Gasket:

Grade "E" EPDM (Color code: Green stripe) Good for cold & hot water up to +230°F (+110°C). Also good for services for water with acid, water with chlorine, deionized water, seawater and waste water, dilute acids, oil-free air and many chemicals. **Not recommended for petroleum oils, minerals oils, solvents and aromatic hydrocarbons.**

Maximum Temperature Range: -30°F (-34°C) to +230°F (+110°C)*.

*EPDM gaskets for water services are not recommended for

steam services unless couplings or components are accessible for frequent gasket replacement.

- Grade "T" Nitrile (Color code: Orange stripe) (Option) Recommended for petroleum products, vegetable oils, mineral oils and air with oil vapors. Temperature range: -20°F to +180°F (-29°C to +82°C). Also good for water services under +150°F (+66°C). **Do not use for HOT WATER above +150°F (+66°C) or HOT DRY AIR above +140°F (+60°C)**

- Other options: Grade "O" Fluoro-Elastomer
Grade "L" Silicone.

• Bolts & Nuts:

Heat treated carbon manganese steel track bolts to ASTM A449-83a (or A183 Gr. 2), minimum tensile strength 110,000 psi (758 MPa), Zinc electroplated, with heavy-duty hexagonal nuts to ASTM A563.

Flow Data – C_v Values

Values for flow of water at +60°F (+16°C).

$$C_v = \frac{Q}{\sqrt{\Delta P}}$$

Where: C_v = Flow coefficient
Q = Flow (GPM)
ΔP = Pressure drop (psi)

Model 7721 Mechanical Tee, Female Threaded Outlet C _v Values			
Nominal Size in / mm	C _v Values	Nominal Size in / mm	C _v Values
½ 15	15	2 50	100
¾ 20	20	2½ 65	125
1 25	25	3 80	200
1¼ 32	45	4 100	350
1½ 40	60		

Flow Characteristics

Model 7721 Mechanical Tee, Female Threaded Outlet Flow Characteristics			
Nominal Size in / mm	Equivalent Length feet/meter of pipe	Nominal Size in / mm	Equivalent Length feet/meter of pipe
½ 15	2.0 0.6	2 50	10.0 3.2
¾ 20	4.0 1.2	2½ 65	20.0 6.0
1 25	5.0 1.5	3 80	27.0 8.1
1¼ 32	6.0 1.8	4 100	35.0 10.5
1½ 40	8.0 2.4		

General Notes:

- **ASME/ANSI Pressure-Temperature Rating** is provided as an aid in selecting a proper coupling to incorporate with other piping components (valves, flanges, and etc.) that are used in the same system and carry the ASME/ANSI rating. Select a Class 150 coupling to incorporate with Class 150 valves and flanges.
- **Maximum Working Pressure (CWP)** listed is the maximum cold water pressure for general piping services tested to ASTM F1476 and or AWWA C606 methods. Figures listed are based on roll- or cut-grooved standard wall carbon steel pipe. For other pipe schedules or pipe materials, contact **Shurjoint** for additional information.
- **Listed and or Approved Pressures** are pressure ratings for fire protection systems, tested and approved by various approval bodies. Please always refer to the latest approval data posted on the **Shurjoint** website.
- **Field Joint Test:** For one time only the system may be tested hydrostatically at 1½ times the maximum working pressure listed (AWWA C606 5.2.3).
- **Warning:** Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- **The 10 Year Limited Warranty** applies to manufacturing defects only and does not cover severe service/temperature applications or wear parts.
- **Shurjoint** reserves the right to change specifications, designs and or standard without notice and without incurring any obligations.

Job Name:	System No.	Location:
Contractor:	Approved:	Date:
Engineer:	Approved:	Date:

Shurjoint product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact **Shurjoint** Technical Service. **Shurjoint** reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligations to make such changes and modifications on **Shurjoint** products previously subsequently sold.